



61.100N | PE Film 100 Total Tape | Application

Features

A high tack transparent polyethylene film of 100 micron, with easy handling and clean pick up of all brands of vinyl. Used to transfer decals and die cut lettering from silicone paper liner to the final surface of application. The special acrylic modified adhesive guarantees an easy transfer letters and very easy removal of the application tape. The transparency of the film allows perfect positioning. Available in rolls of 1220mm x 100m.

Technical & Performance Information

Film Thickness	100 microns
Adhesive Thickness	10 microns
Total Thickness	110 microns
Adhesive Type	Modified acrylic
Release Liner	-
Artificial Weathering*	-
Film Tensile Strength MD	-
Film Elongation MD	-
Adhesion to steel (20 mins / 180°)	3 N/25mm
Adhesion to steel (24 hrs / 180°)	-
Dimensional Stability	< 0.5 mm
Application Temperature	+10 to +40 °C
Service Temperature	-

* equivalent to vertical exposure in Mid-European climate

Warranty

iSee2 warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user stores the material in the original boxes (out of direct sunlight) from our factory. We also recommend to store our material at 21°C with 50% relative humidity. iSee2 only warrants our products to be free from defects in workmanship or defects in iSee2 material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise shall be assumed by the seller or manufacturer. User assumes all risk and liability in connection herewith. All data values quoted above are typical and should not be used to deem the product defective, if measured values are different.

Groendreef 35
B-9880 Aalter | Belgium
T +32 9 216 6700
F +32 9 216 6709
W www.isee2.eu